

VALUE SERIES® V40 SERIES (RIM)

Fill out the blank boxes below and email this pdf to sales@allcctvsupply.com to place order

RATING

For no rating, leave blank

"H" = Hurricane

"F" = Fire Rated (Less/No
Dogging Only)

"FH" = Hurricane and Fire Rated

SERIES TYPE

V40 = Rim device, wide stile

V40xW = Weatherized Rim device,
wide stile (non-electrified)

V40xNS = Rim device, narrow stile

V40xNSxW = Weatherized Rim
device, narrow stile
(non-electrified)

OUTSIDE TRIM FINISH

626 = Brushed chrome (D/WS trims)

628 = Brushed Aluminum (P/PN trims)

689 = Aluminum (BN/A/AN trims)

693 = Black, powder coated (BN/A/AN trims)

711 = Black, Aluminum (P/PN trims)

DEVICE FINISH

628 = Brushed Aluminum*

711 = Black, Aluminum

DOGGING FUNCTION

LD = Less/No dogging

HD = Hex key dogging

CD = Cylinder key dogging

STRIKES

98 = Semi-Mortise
(std. on
V40xNS)

99 = Surface (std.
on V40)

94 = Double-Door
(least secure)

PRE-INSTALLED CYLINDERS

If cylinders provided by others, leave blank

MC65 = Mortise Cylinder(s) 6pin/Keyed 5

IC7 = Mortise Cylinder(s) SFIC housing

IK7 = Mortise Cylinder(s) InstaKey housing

RC65 = Rim Cylinder(s) 6pin/Keyed 5

IC7R = Rim Cylinder(s) SFIC housing

IK7R = Rim Cylinder(s) InstaKey housing

POWER TRANSFERS

FC3 = 3' Flex Conduit

FC10 = 10' Flex Conduit

FC3W = 3' Weatherized
Flex Conduit

FC10W = 10' Weatherized
Flex Conduit

PT5 = Power Transfer

EH8 = Electric Hinge

PUSHPAD COLOR

Contact factory for other
languages and colors

BLK = Black

RWE = Red Pushpad / White
English Lettering

FASTENERS

For Standard machine, wood & self-
drilling screws, leave blank

SN1 = Sex Nuts/Throughbolts
(Hurricane rated
hardware includes sex
nuts for latch bolt)

OUTSIDE TRIM FUNCTION & FINISH

01P = Exit only, blank plate

03P = Key retracts latch

01PN = Exit only, blank plate; narrow trim

03PN = Key retracts latch; narrow trim

03WS = Key retracts latch

02A = Dummy pull

03A = Key retracts pull; pull trim

02AN = Dummy pull; narrow trim

03AN = Key retracts pull - pull trim; narrow trim

02BN = Dummy lever; narrow trim

08BN = Active lever, key locks/unlocks lever;
narrow trim (handed) (classroom)

09BN = Lever trim active by key, locked when
key removed; narrow trim (handed)
(storeroom)

14BN = Active lever, no key cylinder; narrow trim
(handed) (passage)

02D2W = Dummy lever; wide trim (two posts for
use with narrow head device)

08D2W = Active lever, key locks/unlocks lever;
wide trim (two posts for use with narrow
head device) (classroom)

09D2W = Lever trim active by key, locked when
key removed; wide trim (two posts for
use with narrow head device)
(storeroom)

14D2W = Active lever, no key cylinder; wide trim
(two posts for use with narrow head
device) (passage)

EU2W = Electric lock/unlock; wide trim (two posts
for use with narrow head device) -
24VDC & Fail Secure (FSE) Std. -
Specify handing (not field reversible).
For 12VDC specify VDC. For Fail Safe
specify FSA

CBK = Cylinder Bracket Kit, 03 only, plate & pull
handle by others required

DOOR HANDING

RHR = Right hand reverse*

LHR = Left hand reverse

ELECTRIFIED FUNCTION

For no electrified function, leave blank

Standard

Select Arming Time and Auto Rearm

EA = Hardwired Elec. Alarm

(Formerly EH/EHxR)

EB = Elec. Alarm with Battery

ED = Elec. Dogging

EX = Request To Exit (Signal) Switch

EXV = Request To Exit (Current) Switch

EI = Elec. Integration (logic controller
required)

ES = Elec. Switching (dead latch &
OKC switches)

Delayed Egress

Select Arming Delay, Delayed Egress

Time and Silent Arming

EE = Delayed Egress

Delayed Egress Only (EE)

Comes standard with 90-800 power supply

Single = (1) 90-800 w/o bat backup

Pair = (1) 90-800 w/o bat backup

Weatherized Alarms

Select Arming Time and Auto Rearm

EB W = Elec. Battery Operated Exit
Alarm Weatherized

Latch Retraction

ER EX = Elec. Latch Retraction with
Request To Exit Switch (silencer
standard)

ER EX W = Elec. Latch Retraction
Weatherized with Request To
Exit Switch (silencer standard)

Latch Retraction Only (ER & ER W)

(Sold Separately)

Single = 81-800

Pair = 82-800

2 Single = 83-800

Weatherized Others

ER EX W = Elec. Latch Retraction
Weatherized with Request To
Exit Switch (silencer standard)

EX W = Request To Exit (Signal)
Switch Weatherized

EXV W = Request To Exit (Current)
Switch Weatherized

WDE = Weatherized Delayed
Egress (see EasyKits)

NOTE: * = default/standard

Fire-rated trims must be Fail Safe (FSA)

All fire-rated devices Less Dogging/fail safe

Also see online
version at
detex.com/hto

February 28, 2018