

VALUE SERIES® V50 SERIES (SURFACE VERTICAL ROD)

Fill out the blank boxes below and email this pdf to sales@allcctvsupply.com to place order

RATING

For no rating, leave blank

- "H" = Hurricane (V50 & V50xW only)
- "F" = Fire Rated (Less/No Dogging Only)
- "FH" = Hurricane and Fire Rated

SERIES TYPE

- V50** = SVR, wide stile
- V50xW** = Weatherized SVR, wide stile (non-electrified)
- V50xNS** = SVR, narrow stile
- V50xNSxW** = Weatherized SVR, narrow stile (non-electrified)
- V51** = SVR, top rod only, wide stile
- V51xW** = Weatherized SVR, top rod only, wide stile (non-electrified)
- V51xNS** = SVR, top rod only, narrow stile
- V51xNSxW** = Weatherized SVR, top rod only, narrow stile (non-electrified)

OUTSIDE TRIM FINISH

- 626** = Brushed chrome (D/WS trims)
- 628** = Brushed Aluminum (P/PN trims)
- 689** = Aluminum (BN/A/AN trims)
- 693** = Black, powder coated (BN/A/AN trims)
- 711** = Black, Aluminum (P/PN trims)

DOGGING FUNCTION

- LD** = Less/No dogging
- HD** = Hex key dogging
- CD** = Cylinder key dogging

DEVICE FINISH

- 628** = Brushed Aluminum*
- 711** = Black, Aluminum

STRIKES

- 96** = Surface non-roller top strike and non-dust proof bottom strike*
- 96B** = Substitute 96 bottom strike for Dust Proof strike

PRE-INSTALLED CYLINDERS

If cylinders provided by others, leave blank

- MC65** = Mortise Cylinder(s) 6pin/Keyed 5
- IC7** = Mortise Cylinder(s) IC housing
- IK7** = Mortise Cylinder(s) InstaKey housing
- RC65** = Rim Cylinder(s) 6pin/Keyed 5
- IC7R** = Rim Cylinder(s) IC housing
- IK7R** = Rim Cylinder(s) InstaKey housing

Specify KA for Keyed Alike

Trim

Device

PUSHPAD COLOR

Contact factory for other languages and colors

- BLK** = Black
- RWE** = Red Pushpad / White English Lettering

POWER TRANSFERS

- FC3** = 3' Flex Conduit
- FC10** = 10' Flex Conduit
- FC3W** = 3' Weatherized Flex Conduit
- FC10W** = 10' Weatherized Flex Conduit
- PT5** = Power Transfer
- EH8** = Electric Hinge

OUTSIDE TRIM STYLE & FINISH

- 01P** = Exit only, blank plate
- 03P** = Key retracts latch
- 01PN** = Exit only, blank plate; narrow trim
- 03PN** = Key retracts latch; narrow trim
- 03WS** = Key retracts latch
- 02A** = Dummy pull
- 03A** = Key retracts pull; pull trim
- 02AN** = Dummy pull; narrow trim
- 03AN** = Key retracts pull - pull trim; narrow trim
- 02BN** = Dummy lever; narrow trim
- 08BN** = Active lever, key locks/unlocks lever; narrow trim (handed) (classroom)
- 09BN** = Lever trim active by key, locked when key removed; narrow trim (handed) (storeroom)
- 14BN** = Active lever, no key cylinder; narrow trim (handed) (passage)
- 02D2W** = Dummy lever; wide trim (two posts for use with narrow head device)
- 08D2W** = Active lever, key locks/unlocks lever; wide trim (two posts for use with narrow head device) (classroom)
- 09D2W** = Lever trim active by key, locked when key removed; wide trim (two posts for use with narrow head device) (storeroom)
- 14D2W** = Active lever, no key cylinder; wide trim (two posts for use with narrow head device) (passage)
- EU2W** = Electric lock/unlock; wide trim (two posts for use with narrow head device) (24VDC & Fail Secure [FSE] Std.) - Specify handing (not field reversible). For 12VDC specify VDC. For Fail Safe specify FSA
- CBK** = Cylinder Bracket Kit, 03 only, plate & pull handle by others required

DOOR HANDING

- RHR** = Right hand reverse*
- LHR** = Left hand reverse

KEYSTOP

- KS** = Key Stop (Available with EA, EE, EEExER, EI functions)

DOOR WIDTH

- 36"** wide door (3')*
- 48"** wide door (4')

DOOR HEIGHT/SVR HEIGHT

- 84"** high door
- 96"** high door
- 120"** high door

FASTENERS

- For Standard machine, wood & self-drilling screws, leave blank
- SN1** = Sex Nuts/Throughbolts (Hurricane rated hardware includes sex nuts for top latch and bottom bolt)

ELECTRIFIED FUNCTION

For no electrified function, leave blank

Standard

- Select Arming Time and Auto Rearm*
- EA** = Hardwired Elec. Alarm (Formerly EH/EHxR)
- EB** = Elec. Alarm with Battery
- ED** = Elec. Dogging
- EX** = Request To Exit (Signal) Switch
- EXV** = Request To Exit (Current) Switch

Delayed Egress

- Select Arming Delay, Delayed Egress Time and Silent Arming*
- EE** = Delayed Egress

Delayed Egress Only (EE)

- Comes standard with 90-800 power supply*
- Single** = (1) 90-800 w/o bat backup
- Pair** = (1) 90-800 w/o bat backup

Weatherized Alarms

- Select Arming Time and Auto Rearm*
- EB W** = Elec. Battery Operated Exit Alarm Weatherized

Latch Retraction

- ER EX** = Elec. Latch Retraction with Request To Exit Switch (silencer standard)
- ER EX W** = Elec. Latch Retraction Weatherized with Request To Exit Switch (silencer standard)

Latch Retraction Only (ER)

- (Sold Separately)*
- Single** = 81-800
- Pair** = 82-800
- 2 Single** = 83-800

Weatherized Others

- ER EX W** = Elec. Latch Retraction Weatherized with Request To Exit Switch (silencer standard)
- EX W** = Request To Exit (Signal) Switch Weatherized
- EXV W** = Request To Exit (Current) Switch Weatherized
- WDE** = Weatherized Delayed Egress (see EasyKits)

Fire-rated trims must be Fail Safe (FSA)

All fire-rated devices Less Dogging/fail safe

NOTE: * = default/standard

Also see online version at detex.com/hto

January 15, 2019

