

## HARDWARE FEATURES

<b>Interface</b>	8 10/100Mbps RJ45 Ports 2 100/1000Mbps RJ45 Ports
<b>Network Media</b>	10/100/1000 BASE-TX: UTP category 5 or better

## HARDWARE FEATURES

	(maximum 100m)
<b>Fan Quantity</b>	Fanless
<b>Power Budget</b>	120W
<b>Internal Power Supply</b>	AC110-240V 50/60Hz
<b>PoE Ports (RJ45)</b>	Standard: 802.3 af/at/bt compliant PoE Ports: Port1- Port8
<b>Backplane Bandwidth</b>	5.6Gbps
<b>Mac Address Table</b>	4K
<b>Packet Forwarding Rate</b>	4.1Mpps
<b>Buffer</b>	768Kb
<b>Jumbo Frame</b>	10240Bytes
<b>Dimensions</b>	210mm*150mm*35mm (L*W*H)
<b>Protection Leve</b>	Lightning protection 6KV 6KV ESD Contact discharge

## SOFTWARE FEATURES

<b>Transmission Method</b>	Store-And-Forward
<b>Advanced Functions</b>	Priority Function Mac Address Auto-Learning And Auto-Aging Store and forward IEEE 802.3x flow control for Full-duplex Mode Backpressure for Half-duplex Mode

## OTHERS

<b>Certification</b>	CE, FCC, RoHS
<b>Package Contents</b>	POE Switch Electric Line Wall-Mount Kit Guide Book/Warranty Card
<b>Environment</b>	Operating Temperature: -10°C~55°C